


ČELIČNA UŽAD

ČELIČNO UŽE - PLASTIFICIRANO

Šifra	Promjer (mm)	Težina (kg/100m)	Min.prek.sila(kN)	
				1770N/mm ²
19501	1.5-2.5	1.27		1.32
19502	2.0-3.0	2.00		2.35
19503	3.0-4.0	4.02		5.29
19504	3.0-5.0	5.04		5.29
19505	4.0-5.0	6.74		9.41
19506	4.0-6.0	8.00		9.41
19507	5.0-6.0	10.18		14.7
19508	6.0-8.0	16.04		21.1
19509	8.0-10	26.95		37.6
19521	1.5-2.5	1.35		1.43
19522	2.0-3.0	2.14		2.54
19523	3.0-4.0	4.34		5.71
19524	3.0-5.0	5.36		5.71
19525	4.0-5.0	7.31		10.20
19526	4.0-6.0	8.56		10.20
19527	5.0-6.0	11.08		15.90
19528	6.0-8.0	17.34		22.90
19529	8.0-10	29.25		40.60
19541	3.0-4.0	3.91		4.90
19542	3.0-5.0	4.93		4.90
19543	4.0-5.0	6.56		8.70
19544	4.0-6.0	7.82		8.70
19545	5.0-6.0	9.90		13.60
19546	6.0-8.0	15.64		19.60
19547	8.0-10	26.24		34.80
19548	10-12	39.60		54.40
19549	12-14	55.74		78.30
19561	3.0-4.0	4.23		5.29
19562	3.0-5.0	5.25		5.29
19563	4.0-5.0	7.12		9.40
19564	4.0-6.0	8.38		9.40
19565	5.0-6.0	10.78		14.70
19566	6.0-8.0	16.90		21.20
19567	8.0-10	28.48		37.60
19568	10-12	43.10		58.80
19569	12-14	60.80		84.60
19571	2.0-3.0	1.57		1.48
19572	3.0-4.0	3.06		3.33
19573	3.0-5.0	4.08		3.33
19574	4.0-5.0	5.04		5.92
19575	4.0-6.0	6.29		5.92
19576	6.0-8.0	12.22		13.30
19577	8.0-10	20.20		23.70



6x7+KJ PVC/PP/PE



7x7 PVC/PP/PE



6x19+KJ PVC/PP/PE



7x19 PVC/PP/PE



6x12+7KJ PVC/PP/PE

Nije za dizanje!

Završna obrada: Pocičano + PVC/PP/PE
PVC je bezbojni, određena boja po narudžbi
Dopuštena radna temperatura
PVC-a je oko 100°C.



ČELIČNA
UŽAD