


ČELIČNA UŽAD



ČELIČNA UŽAD ZA DIZALICE, KRANOVE, ŠUMARSTVO

Šifra	Promjer užeta mm	Težina kg/100m		Min. prekidna sila(kN)			
		Čvrstoća žice(N/mm2)		1570		1770	
		KJ	ČJ	KJ	ČJ	KJ	ČJ
19401	8	24.3	26.8	33.2	35.8	37.4	40.3
19402	10	38.0	41.8	51.8	55.9	58.4	63.0
19403	12	54.7	60.2	74.6	80.5	84.1	90.7
19404	13	64.2	70.6	87.6	94.5	98.7	106
19405	14	74.5	81.9	102	110	114	124
19406	16	97.3	107	133	143	150	161
19407	18	123	135	168	181	189	204
19408	20	152	167	207	224	234	252
19409	22	184	202	251	271	283	305
19410	24	219	241	298	322	336	363
19411	26	257	283	350	378	395	426
19412	28	298	328	406	438	458	494
19413	30	342	376	466	503	526	567
19414	32	389	428	531	572	(598)	(645)
19415	34	439	483	599	646	(675)	(728)
19416	36	492	542	671	724	(757)	(817)
19417	38	549	604	748	807	(843)	(910)
19418	40	608	669	829	894	—	—
19419	42	670	737	914	986	—	—




6x36WS - DIN 3064 - HRN C.H1.108

Primjena: Kranovi, dizalice, vitla, šumarstvo, priveznice
Završna obrada: Pocičnčano, crno-mašćeno



ČELIČNA
UŽAD

Šifra	Promjer užeta mm	Težina kg/100m		Min. prekidna sila(kN)			
		Čvrstoća žice (N/mm2)		1570		1770	
		KJ	ČJ	KJ	ČJ	KJ	ČJ
19431	6	14.0	15.5	17.5	18.5	19.8	20.9
19432	7	19.1	21.1	23.8	25.2	26.9	28.4
19433	8	25.0	27.5	31.3	33.0	35.1	37.2
19434	9	31.6	34.8	39.4	41.7	44.4	47.0
19435	10	39.0	43.0	48.7	51.5	54.9	58.1
19436	11	47.2	52.0	58.9	62.3	66.4	70.2
19437	12	56.2	61.9	70.1	74.2	79.0	83.6
19438	13	65.9	72.7	82.3	87.0	92.7	98.1
19439	14	76.4	84.3	95.4	101	108	114
19440	16	99.8	110	125	132	140	149
19441	18	126	139	158	167	178	188
19442	20	156	172	195	206	219	232
19443	22	189	208	236	249	266	281
19444	24	225	248	280	297	316	334
19445	26	264	291	329	348	371	392
19446	28	306	337	382	404	430	455
19447	30	351	387	438	463	494	523
19448	32	399	440	498	527	(562)	(594)



DIN 3069 - HRN C H1.115

Primjena: Kranovi i dizalice
Konstrukcija: 19x7+čj
Završna obrada: Pocičnčano, crno-mašćeno.






ČELIČNA UŽAD

ČELIČNA UŽAD ZA LIFTOVE

DIN 3063 - HRN C.H1.104

Primjena: Liftovi
Konstrukcija: 8x19S+KJ,
8X19S+ČJ
Završna obrada:
crna-mašćena






Šifra	Promjer užeta mm	Težina kg/100m	Min. prekidna sila(kN)			
			Čvrstoća žice(N/mm2)			
			1180/1770	1320/1620	1370/1570	1570/1770
19301	8	21.8	25.7	26.5	28.1	30.8
19302	9	27.5	32.5	—	35.6	38.9
19303	9.5	30.7	36.2	37.3	39.7	43.6
19304	10	34.0	40.1	41.3	44.0	48.1
19305	11	41.1	48.6	50.0	53.2	58.1
19306	12	49.0	57.8	59.5	63.3	69.2
19307	12.7	54.8	64.7	66.6	70.9	77.5
19308	13	57.5	67.8	69.8	74.3	81.2
19309	14	66.6	78.7	81.0	86.1	94.2
19310	14.3	69.5	82.1	—	—	98.3
19311	15	76.5	90.3	—	98.9	108
19312	16	87.0	103	106	113	123
19313	17.5	104	123	—	—	147
19314	18	110	130	134	142	156
19315	19	123	145	149	159	173
19316	20	136	161	165	176	192
19317	20.6	144	170	—	—	204
19318	22	165	194	200	213	233

ČELIČNA UŽAD



DIN 3063 8x19S - HRN C.H1.104 8x19W - HRN C.H1.096

Primjena: Liftovi.
Konstrukcija: 8x19S+ČJ
/8x19W+ČJ
/8X25Fi+ČJ
Završna obrada:
crno-mašćeno



Šifra	Promjer užeta mm	Težina kg/100m	Min. prekidna sila(kN)		
			Čvrstoća žice(N/mm2)		
			1180/1770	1370/1570	1570/1770
19331	8	26.0	33.6	35.8	38.0
19332	9	33.0	42.5	45.3	48.2
19333	9.5	36.7	47.4	50.4	53.7
19334	10	40.7	52.5	55.9	59.5
19335	11	49.2	63.5	67.6	79.1
19336	12	58.6	75.6	80.5	85.6
19337	12.7	65.6	84.7	90.1	95.9
19338	13	68.8	88.7	94.5	100
19339	14	79.8	102	110	117
19340	15	91.6	118	126	134
19341	16	104	137	143	152
19342	18	132	170	181	193
19343	19	147	190	202	215
19344	20	163	210	224	238
19345	22	197	254	271	288

